

# LEDINNOVATIE B.V.B.A

## Specification

<b>Model</b>	04303X00X
<b>Lighting source</b>	Lumenmax SMD3014 LED
<b>LED QTY</b>	240-300 pcs
<b>Power consumption</b>	24-30W (includes driver)
<b>Input voltage (Driver)</b>	175-265VAC /50-60HZ
<b>Input voltage (Lighting)</b>	60~70V DC
<b>Constant current</b>	900mA
<b>Efficiency</b>	≥90%
<b>PF</b>	≥0.90
<b>LED Lifespan</b>	≥ 50000H
<b>CCT</b>	3000-5000-6500K
<b>Luminous</b>	1680-2100lm(± 5%)
<b>Luminescence efficiency</b>	>70 lm/w
<b>Beam-angle</b>	120 °
<b>Ra</b>	Ra ≥ 75
<b>Temperature rising</b>	< 20 °C
<b>Operation temperature</b>	-40~+50°C
<b>Relative humidity</b>	10%-80%RH
<b>Fixture Material</b>	Oxidized Aluminum + High Quality PMMA (Acrylic)+PC diffuser
<b>Dimension</b>	595 x 295 x 9 mm
<b>Net Weight (includes driver)</b>	1,8KG
<b>Protection grade</b>	IP44
<b>Insulation class</b>	CLASS II
<b>Environmental</b>	All materials meet with RoHS compliance
<b>Certificate</b>	CE, RoHS